



# IECEX Certificate of Conformity

## INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification System for Explosive Atmospheres

for rules and details of the IECEx Scheme visit [www.iecex.com](http://www.iecex.com)

Certificate No.: **IECEX CSA 25.0040X** Page 1 of 5 [Certificate history:](#)  
Issue 0 (2025-05-19)

Status: **Current** Issue No: 1

Date of Issue: 2025-12-05

Applicant: **I-Care srl**  
Rue Rene Descartes 18  
7000 Mons  
**Belgium**

Equipment: **Wireless Gateway GW900-4G-xx Ex (where xx can be EU or US or GL), Models WG150160H-02 and WG150160L-02 (for EU), Models WG150161H-02 and WG150161L-02 (for US) & Models WG150164H-02, WG150164L-02 (for GL)**

Optional accessory:

Type of Protection: **Increased Safety 'e', Encapsulation 'm'**

Marking: Ex eb mb IIC T4 Gb  
-15 °C ≤ Tamb ≤ 60 °C

Approved for issue on behalf of the IECEx  
Certification Body:

**Dave Magee**

Position:

**Senior Director of Operations**

Signature:  
(for printed version)

Date:  
(for printed version)

1. This certificate and schedule may only be reproduced in full.
2. This certificate is not transferable and remains the property of the issuing body.
3. The Status and authenticity of this certificate may be verified by visiting [www.iecex.com](http://www.iecex.com) or use of this QR Code.



Certificate issued by:

**CSA Group**  
178 Rexdale Boulevard  
Toronto, Ontario M9W 1R3  
Canada





# IECEX Certificate of Conformity

Certificate No.: **IECEX CSA 25.0040X**

Page 2 of 5

Date of issue: 2025-12-05

Issue No: 1

Manufacturer: **I-Care srl**  
Rue Rene Descartes 18  
7000 Mons  
**Belgium**

Manufacturing  
locations: **I-Care srl**  
Bd. Initialis 5  
7000 Mons  
**Belgium**

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEX Quality system requirements. This certificate is granted subject to the conditions as set out in IECEX Scheme Rules, IECEX 02 and Operational Documents as amended

#### STANDARDS :

The equipment and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards

[IEC 60079-0:2017](#) Explosive atmospheres - Part 0: Equipment - General requirements  
Edition:7.0

[IEC 60079-18:2017](#) Explosive atmospheres - Part 18: Protection by encapsulation "m"  
Edition:4.1

[IEC 60079-7:2017](#) Explosive atmospheres - Part 7: Equipment protection by increased safety "e"  
Edition:5.1

This Certificate **does not** indicate compliance with safety and performance requirements other than those expressly included in the Standards listed above.

#### TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in:

Test Reports:

[CA/CSA/ExTR25.0020/00](#)

[CA/CSA/ExTR25.0020/01](#)

Quality Assessment Report:

[DE/TUR/QAR16.0004/06](#)



# IECEX Certificate of Conformity

Certificate No.: **IECEX CSA 25.0040X**

Page 3 of 5

Date of issue: 2025-12-05

Issue No: 1

## **EQUIPMENT:**

Equipment and systems covered by this Certificate are as follows:

The Wireless Gateway WG900-4G-xx Ex is networking hardware for fixed installations designed to receive data via the OpenThread wireless protocol from compatible measurement devices (the certification of which is not covered by this certificate) and transmit it over a cellular network. The device is available in both 100-240 VAC and 24 VDC power configurations. The device is intended for use in explosive atmospheres and is designed with the following ignition protection types:

- Encapsulation (Ex m): Electrical components are encapsulated to prevent the release of sparks or heat that could ignite the surrounding atmosphere.
- Increased Safety (Ex e): The encapsulated block is housed within a Ex e enclosure, providing enhanced ruggedness and electrical insulation.

The enclosure is non-metallic and has a cable entry for cable connection. The enclosure provides IP64 protection. The cable connection is made via a suitably certified cable gland.

**See annexe for more information**

## **SPECIFIC CONDITIONS OF USE: YES as shown below:**

1. Under certain extreme circumstances, the non-metallic parts incorporated in the enclosure of this equipment may generate an ignition-capable level of electrostatic charge. Therefore, the equipment shall not be installed in a location where the external conditions are conducive to the build-up of electrostatic charge on such surfaces. In addition, the equipment shall only be cleaned with a damp cloth.
2. This equipment shall be installed where the risk of damage to the equipment due to impact is considered to be low.
3. The prospective short circuit current shall be less than 1500 A for AC supply and 100 A for DC supply.



# IECEX Certificate of Conformity

Certificate No.: **IECEX CSA 25.0040X**

Page 4 of 5

Date of issue: 2025-12-05

Issue No: 1

## Equipment (continued):

### Conditions of Manufacture

1. In accordance with IEC 60079-18:2017 clause 9.1, each manufactured item shall be subjected to a visual inspection. No damage shall be evident, such as cracks in the compound, exposure of the encapsulated parts, flaking, inadmissible shrinkage, swelling, decomposition, failure of adhesion or softening.
2. The equipment incorporates previously certified cable glands. It is therefore the responsibility of the manufacturer to continually monitor the status of the certification associated with these devices. The manufacturer shall inform CSA of any modifications to the devices that may impinge upon the explosion safety design of the equipment.



# IECEX Certificate of Conformity

Certificate No.: **IECEX CSA 25.0040X**

Page 5 of 5

Date of issue: 2025-12-05

Issue No: 1

## **DETAILS OF CERTIFICATE CHANGES (for issues 1 and above)**

**Issue 1** – this Issue introduced the following changes:

1. Alternative power supply components (AC & DC)
2. Alternative 4G cellular module
3. GL models are introduced

## **Annex:**

[IECEX CSA 25.0040X Iss 1 Annexe\\_1.pdf](#)

Annexe to: IECEx CSA 25.0040X Issue 1

Applicant: I-Care srl



Apparatus: Wireless Gateway GW900-4G-xx Ex (where xx can be EU or US or GL),  
Models WG150160H-02 and WG150160L-02 (for EU),  
Models WG150161H-02 and WG150161L-02 (for US) &  
Models WG150164H-02, WG150164L-02 (for GL)

**EQUIPMENT (continued)**

The options for the cable gland are as follows:

Manufacturer	Type	Certificate Numbers	Ex Type	Standards
U.I. Lapp GmbH	SKINTOP KR-M, p/n 54115225 or SKINTOP K-M, p/n 54115220	IECEX IBE 13.0027X	Ex eb IIC	IEC 60079-0:2011 IEC 60079-7:2006
PFLITSCH GmbH & Co. KG	LevelEx series, Lex 220ms HTS	IECEX PTB 18.0001X	Ex eb IIC	IEC 60079-0:2017 IEC 60079-7:2017
Pepperl+Fuchs SE	CG.NA.M20S.BN.C.16.K01	IECEX IMQ 14.0004X	Ex eb IIC	IEC 60079-0:2017 IEC 60079-7:2017

The models covered are as follows:

Designation	Model number	Ratings
Wireless Gateway GW900-4G-EU Ex	WG150160H-02	100 – 240 Vac, 50/60 Hz, 1.8 W
	WG150160L-02	24 Vdc, 1.8 W
Wireless Gateway GW900-4G-US Ex	WG150161H-02	100 – 240 Vac, 50/60 Hz, 1.8 W
	WG150161L-02	24 Vdc, 1.8 W
Wireless Gateway GW900-4G-GL Ex	WG150164H-02	100 – 240 Vac, 50/60 Hz, 1.8 W
	WG150164L-02	24 Vdc, 1.8 W