



Certificate of Compliance

Certificate: 80218472 **Master Contract:** 304650
Project: 80272252 **Date Issued:** 2026-01-21
Issued to: I-care SRL **Issued by:** Ian Henderson
Rue Descartes 18 Ian Henderson
Mons, Walloon Brabant 7000
Belgium
Attention: Ulrich Weinsdoerfer

The products listed below are eligible to bear the CSA Mark shown with adjacent indicators 'C' and 'US' for Canada and US or with adjacent indicator 'US' for US only or without either indicator for Canada only.



PRODUCTS

Class 2258 02 PROCESS CONTROL EQUIPMENT - For Hazardous Locations
Class 2258 82 PROCESS CONTROL EQUIPMENT - For Hazardous Locations - Certified to US Standards

Class I, Division 2, Group A, B, C, D
Class II, Division 2 Groups EFG, Class III;
Ex eb mb IIC T4 Gb
Class I, Zone 1, AEx eb mb IIC T4 Gb

Wireless Gateway GW900-4G-US Ex

Model(s)	Rated Voltage (VAC)	Frequency (Hz)	Rated Power (W)
WG150161H-02	100 - 240	50/60	1.8



Certificate: 80218472

Master Contract: 304650

Project: 80272252

Date Issued: 2026-01-21

Class I, Division 2, Group A, B, C, D
Class II, Division 2 Groups EFG, Class III;
Ex eb mb IIC T4 Gb
Class I, Zone 1, AEx eb mb IIC T4 Gb

Model(s)	Rated Voltage (VDC)	Rated Power (W)
WG150161L-02	24	1.8

APPLICABLE REQUIREMENTS

CSA C22.2 No. 62368-1:19 - Third Edition - Audio/video, information and communication technology equipment - Part 1: Safety requirements - Including Update No 1 - October 2021

CAN/CSA-C22.2 No. 213-17 + UPD 1 (2018) + UPD 2 (2019) + UPD 3 (2021) (R2022) - Non-incendive Electrical Equipment for Use in Class I and II, Division 2 and Class III, Divisions 1 and 2 Hazardous (Classified) Locations

CSA C22.2 No. 60079-0:19 - Fourth Edition - Explosive atmospheres - Part 0: Equipment - General requirements

CAN/CSA C22.2 No. 60079-7:16 + AMD1:2018 (R2021) - Explosive atmospheres - Part 7: Equipment protection by increased safety 'e'

CSA C22. No. 60079-18:16 - Second Edition - Explosive atmospheres - Part 18: Equipment protection by encapsulation 'm'

UL 62368-1:2019 - Third Edition - Safety Audio/video, information and communication technology equipment – Part 1: Safety requirements

ANSI/UL 121201:2017 - Ninth Edition - Including Revisions Through April 1, 2021 - UL Standard for Safety Nonincendive Electrical Equipment for Use in Class I and II, Division 2 and Class III, Divisions 1 and 2 Hazardous (Classified) Locations

ANSI/UL 60079-0:2020 - Seventh Edition - Including revisions through July 19, 2024 - Explosive Atmospheres – Part 0: Equipment – General Requirements

ANSI/UL 60079-7:2017 - Fifth Edition - Including revisions through June 3, 2021 - Explosive Atmospheres – Part 7: Equipment protection by increased safety "e"

UL 60079-18 - Explosive Atmospheres – Part 18: Equipment Protection by Encapsulation 'm' - Fourth Edition; Reprint with Revisions Through and Including June 9, 2023

Conditions Of Acceptability

1. Under certain extreme circumstances, the non-metallic parts incorporated in the enclosure of this equipment may generate an ignition-capable level of electrostatic charge. Therefore, the equipment shall not be installed in a location where the external conditions are conducive to the build-up of electrostatic charge on such surfaces. In addition, the equipment shall only be cleaned with a damp cloth.
2. This equipment shall be installed where the risk of damage to the equipment due to impact is considered to be low.
3. The prospective short circuit current shall be less than 1500 A for AC supply and 300 A for DC supply.



Certificate: 80218472

Master Contract: 304650

Project: 80272252

Date Issued: 2026-01-21

-
4. The product was tested in a branch circuit protected by a 20 A circuit breaker. Additional evaluation shall be conducted if a higher protector is to be used in the end system

Markings

The manufacturer is required to apply the following markings:

- Products shall be marked with the markings specified by the particular product standard.
- Products certified for Canada shall have all Caution and Warning markings in both English and French.

Additional bilingual markings not covered by the product standard(s) may be required by the Authorities Having Jurisdiction. It is the responsibility of the manufacturer to provide and apply these additional markings, where applicable, in accordance with the requirements of those authorities.

The products listed are eligible to bear the CSA Mark shown with adjacent indicators 'C' and 'US' for Canada and US (indicating that products have been manufactured to the requirements of both Canadian and U.S. Standards) or with adjacent indicator 'US' for US only or without either indicator for Canada only.

- The CSA Mark with adjacent C_US qualifiers
- Manufacturer
- Model designation
- CSA certificate number : CSA 25CA80218472X
- Serial number and a date code that is traceable to the year of manufacture
- The hazardous location designation (See 'PRODUCTS' section)
- The temperature class (See 'PRODUCTS' section)
- The ambient temperature range (See 'PRODUCTS' section)
- The following warnings (These warnings are also marked in French):

WARNING – READ MANUAL

WARNING – POTENTIAL ELECTROSTATIC CHARGING HAZARD



Certificate: 80218472


Master Contract: 304650

Project: 80272252

Date Issued: 2026-01-21

Notes:

Products certified under Class(es) C225802, C225882 have been certified under CSA's ISO/IEC 17065 accreditation with the Standards Council of Canada (SCC). www.scc.ca





Supplement to Certificate of Compliance

Certificate: 80218472

Master Contract: 304650

*The products listed, including the latest revision described below,
are eligible to be marked in accordance with the referenced Certificate.*

Product Certification History

Project	Date	Description
80272252	2026-01-21	Variation to CSA 25CA80218472X to; - Introduce new variants (only changes - alternative power supply modules, alternative 4G cellular module). - Add "Class II Division 2', Class III' marking for dust
80218472	2025-08-22	Original cCSAus certification of Class I, Division 2 non-incendive, encapsulation "mb" and Ex eb protected Wireless Gateway GW900-4G-US Ex Models WG150161H-02 and WG150161L-02.